Application/Control Number: 09/966,081 Docket No.: 2000-0573

Art Unit: 2626

AMENDMENT

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

 (currently amended) A method of rescoring the results of automatic speech recognition, comprising:

generating a plurality of lattices for received speech utterances associated with filling in a plurality of <u>user selected</u> data fields in a <u>user interface</u>;

concatenating the plurality of lattices into a single concatenated lattice; and applying at least one language model to the single concatenated lattice in order to determine relationships between the plurality of lattices.

- 2. (previously presented) The method of rescoring the results of automatic speech recognition according to claim 1, further comprising generating a confidence score after applying the at least one speech recognition model to determine whether the plurality of lattices are acceptable.
- 3. (original) The method of rescoring the results of automatic speech recognition according to claim 2, wherein the confidence score is compared to a predetermined value in order to determine whether to perform the automatic speech recognition process again.
- 4. (original) The method of rescoring the results of automatic speech recognition according to claim 3, wherein the automatic speech recognition process is performed again if the confidence score is less than the predetermined value.

2

Application/Control Number: 09/966,081 Docket No.: 2000-0573

Art Unit: 2626

5. (original) The method of rescoring the results of automatic speech recognition according to claim 1, wherein the rescoring is performed after a speech recognition model has been

compensated to reflect acoustic environmental data and transducer data.

6. (original) The method of rescoring the results of automatic speech recognition according to

claim 1, wherein the rescoring the automatic speech recognition is used in a mobile

communications system.

7. (original) The method of rescoring the results of automatic speech recognition according to

claim 1, wherein the rescoring the automatic speech recognition is used in a satellite

communications system.

8. (currently amended) A rescoring process used in the automatic speech recognition system.

comprising:

a speech recognizer that generates a plurality of lattices, each lattice corresponding to a

received speech utterance associated with filling in one of a plurality of $\underline{user\ selected}$ data fields

in a user interface, by using at least one speech recognition model; and

a controller that concatenates the plurality of lattices into a single concatenated lattice,

and applies the at least one language model to the single concatenated lattice.

9. (original) The rescoring process used in the automatic speech recognition system according to

claim 8, wherein the speech utterances are received from a mobile device.

10. (original) The rescoring process used in an automatic speech recognition system according

to claim 8, wherein the speech utterances are received from a personal digital assistant.

3

Application/Control Number: 09/966,081 Docket No.: 2000-0573

Art Unit: 2626

11. (original) The rescoring process used in an automatic speech recognition system according

to claim 8, wherein the rescoring process used in the automatic speech recognition is used in a

satellite communications system.

12. (original) The rescoring process used in an automatic speech recognition system according

to claim 8, wherein the speech recognition model is a hidden Markov model.

13. (original) The rescoring process used in an automatic speech recognition system according

to claim 8, wherein the controller is a network server.

14. (currently amended) A controller used for rescoring results of an automatic speech

recognition system, comprising:

a first section that generates a plurality of lattices, each lattice associated with a received

speech utterance for filling in one of a plurality of user selected data fields in a user interface;

a second section that concatenates the plurality of lattices into a single concatenated

lattice; and

a third section that applies at least one language model to the single concatenated lattice.

15. (original) The controller used for the rescoring results of the automatic speech recognition

system according to claim 14, the controller further comprising a fourth section that determines

whether an automatic speech recognition process should be performed again.

16. (original) The controller used for the rescoring results of the automatic speech recognition

system according to claim 14, wherein the controller is a network server used in a mobile

communications system.

4